

**Artikel Nr.: 180514**

Netzgerät, BASIC, CC, CC70018/18W



IP20 CE

**Elektrische Daten**

Betriebsart	stromkonstant	Eingangsspannung	220-240V AC/50-60Hz
Leistung	1,40-18,00 W	Leistungsfaktor	0,80C
Ausgangsspannung	2-26V DC	Anschlußmöglichkeit	Klemme
Ausgangsstrom	700 mA		



**Produkteigenschaften**

Schutzklasse II	Überspannungsschutz
SELV Schutzkleinspannung	Lampenbetriebsgerät 110
Kurzschlußfest	Möbeleinbau geeignet
Überlastschutz	ErP Standby-Stromverbrauch < 0,5 W
Übertemperaturschutz	LVD Sicherheit nach EN 61347
Sicherheitstrafo	EMC Funkentstörung + Störfestigkeit nach EN 55015 + EN 61547
nicht dimmbar	EMC Netzstromoberwellen + Flicker nach EN 61000-3-2 + EN 61000-3-3

Schwarze Felder sind zutreffend / graue Felder sind nicht zutreffend

**Artikel Nr.: 180514**

Netzgerät, BASIC, CC, CC70018/18W

**Abmessungen und Gewicht****Grenzwerte**

Länge	115,00 mm	Betriebstemperatur	-20°C - +50°C
Breite	45,00 mm	Gehäusetemperatur	85,00
Höhe	21,00 mm		
Durchmesser	0,00 mm		
Gewicht	87 g		

Article No.: 180514

Power supply unit, BASIC, CC, CC70018/18W



IP20 CE

**Electrical Characteristics**

Operating mode	constant current	Input voltage	220-240V AC/50-60Hz
Power	1,40-18,00 W	Power factor	0,80C
Output voltage	2-26V DC	Connection possibility	clamp
Output current	700 mA		



**Product features**

	Protection class II		Overvoltage protection
SELV	Low voltage protection		Lamp control gear 110
	Short circuit protection		Suitable for furniture installation
	Overload protection	ErP	Standby-power consumption < 0,5 W
	Overheating protection	LVD	Safety according to EN 61347
	Safety transformer	EMC	Interference suppression + immunity according to EN 55015 + EN 61547
	not dimmable	EMC	Mains harmonics + flicker according to EN 61000-3-2 + EN 61000-3-3

Black fields are applicable / gray fields are not applicable

**Article No.: 180514**

Power supply unit, BASIC, CC, CC70018/18W

**Dimensions & Weight****Absolute maximum ratings**

Length	115,00 mm	Operating temperature	-20°C - +50°C
Width	45,00 mm	Case temperature	85,00
Height	21,00 mm		
Diameter	0,00 mm		
Product weight	87 g		