

Deko Light GmbH 342077 Pendelleuchte 342077 / UGR-Tabelle

Leuchte: Deko Light GmbH 342077 Pendelleuchte 342077

Lampen: 1 x Ceiling-/Lamp

| Blendungsbewertung nach UGR | | | | | | | | | | | |
|--|-----|---------------------------------------|------|------|------|------|--|------|------|------|------|
| ρ Decke | | 70 | 70 | 50 | 50 | 30 | 70 | 70 | 50 | 50 | 30 |
| ρ Wände | | 50 | 30 | 50 | 30 | 30 | 50 | 30 | 50 | 30 | 30 |
| ρ Boden | | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 |
| Raumgröße X Y | | Blickrichtung quer zur Lampenachse | | | | | Blickrichtung längs zur Lampenachse | | | | |
| 2H | 2H | 13.7 | 14.6 | 14.6 | 15.5 | 16.6 | 15.6 | 16.5 | 16.5 | 17.4 | 18.5 |
| | 3H | 15.5 | 16.3 | 16.4 | 17.2 | 18.4 | 17.8 | 18.6 | 18.7 | 19.5 | 20.6 |
| | 4H | 16.2 | 17.0 | 17.1 | 17.9 | 19.1 | 18.7 | 19.4 | 19.6 | 20.4 | 21.5 |
| | 6H | 16.8 | 17.5 | 17.7 | 18.4 | 19.6 | 19.5 | 20.2 | 20.4 | 21.1 | 22.3 |
| | 8H | 17.0 | 17.6 | 17.9 | 18.6 | 19.8 | 19.8 | 20.4 | 20.7 | 21.4 | 22.6 |
| | 12H | 17.1 | 17.7 | 18.1 | 18.7 | 19.9 | 20.0 | 20.6 | 20.9 | 21.5 | 22.8 |
| 4H | 2H | 14.7 | 15.5 | 15.6 | 16.4 | 17.6 | 16.1 | 16.8 | 17.0 | 17.8 | 18.9 |
| | 3H | 16.6 | 17.2 | 17.6 | 18.2 | 19.4 | 18.5 | 19.1 | 19.4 | 20.0 | 21.2 |
| | 4H | 17.4 | 18.0 | 18.4 | 19.0 | 20.2 | 19.5 | 20.1 | 20.5 | 21.0 | 22.3 |
| | 6H | 18.1 | 18.6 | 19.1 | 19.6 | 20.8 | 20.4 | 20.9 | 21.4 | 21.9 | 23.2 |
| | 8H | 18.3 | 18.8 | 19.3 | 19.8 | 21.0 | 20.8 | 21.3 | 21.8 | 22.2 | 23.5 |
| | 12H | 18.5 | 18.9 | 19.5 | 19.9 | 21.2 | 21.1 | 21.5 | 22.1 | 22.5 | 23.8 |
| 8H | 4H | 17.9 | 18.4 | 18.9 | 19.3 | 20.6 | 19.7 | 20.1 | 20.7 | 21.1 | 22.4 |
| | 6H | 18.8 | 19.1 | 19.8 | 20.1 | 21.4 | 20.8 | 21.2 | 21.8 | 22.2 | 23.5 |
| | 8H | 19.1 | 19.4 | 20.1 | 20.4 | 21.7 | 21.3 | 21.6 | 22.3 | 22.6 | 23.9 |
| | 12H | 19.4 | 19.6 | 20.4 | 20.6 | 22.0 | 21.7 | 21.9 | 22.7 | 23.0 | 24.3 |
| 12H | 4H | 18.0 | 18.4 | 19.0 | 19.4 | 20.7 | 19.7 | 20.1 | 20.7 | 21.1 | 22.4 |
| | 6H | 18.9 | 19.2 | 19.9 | 20.2 | 21.6 | 20.8 | 21.2 | 21.9 | 22.2 | 23.5 |
| | 8H | 19.3 | 19.6 | 20.3 | 20.6 | 21.9 | 21.4 | 21.6 | 22.4 | 22.7 | 24.0 |
| Variation der Beobachterposition für Leuchtenabstände S | | | | | | | | | | | |
| S = 1.0H | | +0.1 / -0.1 | | | | | +0.1 / -0.1 | | | | |
| S = 1.5H | | +0.2 / -0.2 | | | | | +0.2 / -0.2 | | | | |
| S = 2.0H | | +0.4 / -0.5 | | | | | +0.3 / -0.4 | | | | |
| Standardtabelle | | BK07 | | | | | BK08 | | | | |
| Korrektursummand | | 3.4 | | | | | 6.1 | | | | |
| Korrigierte Blendindizes bezogen auf 5997lm Gesamtlichtstrom | | | | | | | | | | | |

Die UGR-Werte werden gemäß CIE Publ. 117 berechnet. Spacing-to-Height-Ratio = 0.25.