

Deko Light GmbH 707076 Ain Spot 30W 707076 / UGR-Tabelle

Leuchte: Deko Light GmbH 707076 Ain Spot 30W 707076
Lampen: 1 x Track system3-Phases

Blendungsbewertung nach UGR											
ρ Decke		70	70	50	50	30	70	70	50	50	30
ρ Wände		50	30	50	30	30	50	30	50	30	30
ρ Boden		20	20	20	20	20	20	20	20	20	20
Raumgröße X Y		Blickrichtung quer zur Lampenachse					Blickrichtung längs zur Lampenachse				
2H	2H	14.7	15.3	15.0	15.5	15.7	15.8	16.4	16.0	16.6	16.8
	3H	14.6	15.2	14.9	15.4	15.6	15.6	16.2	15.9	16.4	16.7
	4H	14.5	15.0	14.8	15.3	15.6	15.6	16.1	15.9	16.4	16.6
	6H	14.4	14.9	14.8	15.2	15.5	15.5	16.0	15.8	16.3	16.5
	8H	14.4	14.9	14.7	15.2	15.5	15.5	15.9	15.8	16.2	16.5
	12H	14.4	14.8	14.7	15.1	15.4	15.4	15.9	15.8	16.2	16.5
4H	2H	14.5	15.0	14.8	15.3	15.6	15.6	16.1	15.9	16.4	16.6
	3H	14.4	14.8	14.7	15.1	15.4	15.4	15.9	15.8	16.2	16.5
	4H	14.3	14.7	14.7	15.0	15.3	15.3	15.7	15.7	16.1	16.4
	6H	14.2	14.5	14.6	14.9	15.3	15.3	15.6	15.7	15.9	16.3
	8H	14.2	14.5	14.6	14.8	15.2	15.2	15.5	15.6	15.9	16.3
	12H	14.1	14.4	14.6	14.8	15.2	15.2	15.4	15.6	15.8	16.2
8H	4H	14.2	14.5	14.6	14.8	15.2	15.2	15.5	15.6	15.9	16.3
	6H	14.1	14.3	14.5	14.7	15.2	15.1	15.3	15.6	15.8	16.2
	8H	14.0	14.2	14.5	14.6	15.1	15.1	15.3	15.6	15.7	16.2
	12H	14.0	14.1	14.5	14.6	15.1	15.0	15.2	15.5	15.6	16.1
12H	4H	14.1	14.4	14.6	14.8	15.2	15.2	15.4	15.6	15.8	16.2
	6H	14.0	14.2	14.5	14.6	15.1	15.1	15.3	15.6	15.7	16.2
	8H	14.0	14.1	14.5	14.6	15.1	15.0	15.2	15.5	15.6	16.1
Variation der Beobachterposition für Leuchtenabstände S											
S = 1.0H		+6.7 / -27.4					+6.6 / -29.2				
S = 1.5H		+9.5 / -29.4					+9.4 / -31.7				
S = 2.0H		+11.5 / -31.2					+11.4 / -33.3				
Standardtabelle		BK00					BK00				
Korrektursummand		-3.9					-2.9				
Korrigierte Blendindizes bezogen auf 2391lm Gesamtlichtstrom											

Die UGR-Werte werden gemäß CIE Publ. 117 berechnet. Spacing-to-Height-Ratio = 0.25.