

Artikel Nr.: 862056

Netzgerät, BASIC, CV, Q3-24V-100W












IP20 CE

Elektrische Daten

Betriebsart	spannungskonstant	Eingangsspannung	100-240V AC/50-60Hz
Leistung	100,00 W	Leistungsfaktor	>0,95
Ausgangsspannung	24V DC	Anschlußmöglichkeit	Klemme
Ausgangsstrom	0-4160 mA		


Produkteigenschaften

	Schutzklasse II		Überspannungsschutz
SELV	Schutzkleinspannung		Lampenbetriebsgerät 110
	Kurzschlußfest		Möbeleinbau geeignet
	Überlastschutz	ErP	Standby-Stromverbrauch < 0,5 W
	Übertemperaturschutz	LVD	Sicherheit nach EN 61347
	Sicherheitstrafo	EMC	Funkentstörung + Störfestigkeit nach EN 55015 + EN 61547
	nicht dimmbar	EMC	Netzstromoberwellen + Flicker nach EN 61000-3-2 + EN 61000-3-3

Schwarze Felder sind zutreffend / graue Felder sind nicht zutreffend

Artikel Nr.: 862056


Netzgerät, BASIC, CV, Q3-24V-100W

**Abmessungen und Gewicht****Grenzwerte**

Länge	184,00 mm	Betriebstemperatur	-20°C - +50°C
Breite	61,00 mm	Gehäusetemperatur	85,00
Höhe	32,00 mm		
Durchmesser	0,00 mm		
Gewicht	320 g		

Article No.: 862056

Power supply unit, BASIC, CV, Q3-24V-100W












IP20 **CE**

Electrical Characteristics

Operating mode	constant voltage	Input voltage	100-240V AC/50-60Hz
Power	100,00 W	Power factor	>0,95
Output voltage	24V DC	Connection possibility	clamp
Output current	0-4160 mA		


Product features

	Protection class II		Overvoltage protection
SELV	Low voltage protection		Lamp control gear 110
	Short circuit protection		Suitable for furniture installation
	Overload protection	ErP	Standby-power consumption < 0,5 W
	Overheating protection	LVD	Safety according to EN 61347
	Safety transformer	EMC	Interference suppression + immunity according to EN 55015 + EN 61547
	not dimmable	EMC	Mains harmonics + flicker according to EN 61000-3-2 + EN 61000-3-3

Black fields are applicable / gray fields are not applicable

Article No.: 862056

Power supply unit, BASIC, CV, Q3-24V-100W

**Dimensions & Weight**

Length	184,00 mm
Width	61,00 mm
Height	32,00 mm
Diameter	0,00 mm
Product weight	320 g

Absolute maximum ratings

Operating temperature	-20°C - +50°C
Case temperature	85,00